



↑ Uno double steel doors | Distance 22"×64" right and left door/glass ■ Gentek, Black 525



Distance

NEW

V-Groove — Contemporary style

Distance features sandblasted glass with engraved perpendicular V-Groove lines. Its finesse and elegance perfectly match any facade, making a striking statement when used as double doors adding a touch of refined beauty to any entrance.

Privacy level

4/5

Lots of privacy with some clear areas.

Textures

1. Sandblasted finish
2. Polished V-Groove lines



Price index

\$

Distance — V-Groove — Contemporary style

Materials and composition

Double glazing with energy-efficient glass (Low-E), argon gas and intercept® warm edge spacer. This composition reduces condensation, heat transfer by convection, and improves energy efficiency.

Pairing

Looks great when paired with sandblasted finish glass sidelites and transoms.

Custom doorglass

This model is available in custom sizes. Keep the clear V-Groove lines on sandblasted finish glass or choose a unpolished V-Groove line on clear glass.

ENERGY STAR®

This doorglass can be part of an ENERGY STAR-approved entry door system, depending on the options selected. Check with your retailer to see if your selection of Novatech products (door, window frame and doorglass) is ENERGY STAR certified.

Warranty

10-year limited warranty

Frames



Contemporary profile
Contemporary
Contemporary hybrid
Resin
Resin B&W



Classic profile
NovaPVC hybrid
NovaPVC
NovaPVC stainable

Standard sizes



22" x 64" Left

22" x 64" Right

7" x 64"

22" x 48" Left

22" x 48" Right

8" x 48"

22" x 36" Left

22" x 36" Right

8" x 36"

E Can meet the requirements of the ENERGY STAR® program

06-422-XXX-XXX Add this prefix to the codes below.

Glazing	Frames	22" x 64" Left	22" x 64" Right	7" x 64" Sidelite	22" x 48" Left	22" x 48" Right	8" x 48" SL	22" x 36" Left	22" x 36" Right	8" x 36" SL
1" double glazed, 1x Low-E	Contemporary	060-010	060-003	005-003 ²	057-010	057-003	017-003 E	050-010 E	050-003 E	010-003 E
1" double glazed, 1x Low-E	Contemporary hybrid	060-011	060-004	005-004 ¹	057-011	057-004	017-004 ²	050-011 E ¹	050-004 E ¹	010-004 E
1" double glazed, 1x Low-E	Resin	060-013	060-006	005-006 ²	057-013	057-006	—	050-013 E	050-006 E	010-006 E
1" double glazed, 1x Low-E	NovaPVC	060-008	060-001	005-001 ²	057-008	057-001	017-001 E	050-008 E	050-001 E	010-001 E
1" Double Glazed, 1x Low-E	NovaPVC stainable	060-009	060-002	005-002 ²	057-009	057-002	017-002 E	050-009 E	050-002 E	010-002 E
1" double glazed, 1x Low-E	NovaPVC hybrid	060-012	060-005	005-005 ¹	057-012	057-005	017-005 ²	050-012 E ¹	050-005 E	010-005 E

¹ Can meet the requirements of the ENERGY STAR® program only in N300, N600 ou N700 doors. (Sidelites excluded)

² 7" x 64" and 8" x 48" sizes can meet ENERGY STAR® requirements when inserted in a door.

High Performance Door **NHP**

Glazing	Frames	22" x 64" Left	22" x 64" Right	7" x 64"	22" x 48" Left	22" x 48" Right	22" x 36" Left	22" x 36" Right
1.5" triple glazed, 1x low-E	Contemporary							
1.5" triple glazed, 1x low-E	Contemporary hybrid							
1.5" triple glazed, 1x low-E	NovaPVC							
1.5" triple glazed, 1x low-E	NovaPVC hybrid							

On request **E**